Datasheet S32 Gateway

(ESP32 Standard WiFi edition) V2.0



Product identification	
Product brand	BBQKees Electronics
Product name	Gateway S32 (ESP32 Standard WiFi edition)
Product SKU	gw-kit-S32
GTIN	8719327747513
HS Code	84718000
Manufactured in	The Netherlands







Product features (with EMS-ESP 3.5)	
Circuit board version	V2.0 2022
Microcontroller	Espressif ESP32 with 16MB Flash
Firmware	EMS-ESP32 (currently version 3.5)
Bus interface	3.5mm EMS service jack, 2-pin screw terminal
Bus protocol	Bosch EMS and all derivatives like EMS2, EMS+, EMS
	Plus, Heatronic 3.
WiFi	2.4 GHz
Communication protocols	Web interface, MQTT, HTTP RestAPI
MQTT features	Receive data and send commands.
	MQTT discovery for Home Assistant, Domoticz and
	OpenHAB.
HTTP RestAPI	Receive data and send commands via secure interface.

Temperature sensors	Possible to add Dallas temperature sensors. Number of
	sensors depending on wire length. Usually about 10
	sensors. Firmware has no upper limit.

Electrical specifications	
Power supply	7-3VDC via 5.5/2.1mm barrel jack plug
	or 3.5mm EMS service jack
EMS bus	14-16V (14.5 VDC nominal)
Power	<1W
Temperature sensors	All Dallas DS18B20 types, parasitic and non-parasitic
	mode. 3,3V DC.
USB	CH340 chip,
	Internal micro-USB header only for programming

Mechanical specifications	
Enclosure dimensions (LxWxH)	90 x 50 x 24 mm
Enclosure color	dark grey
Enclosure material	ABS plastic, Fire class UL 94 V-0
Weight	0,1kg

Included accessories	3-pin JST ZH plug with 10cm cable,
	30x30mm double sided tape,
	getting started card.
Optional accessories	EMS service jack cable 50cm and 110cm,
	wall mount bracket,
	12V DC 1A power supply with 5.5/2.1mm barrel jack
	plug.